

Solvent

Reference: TDSOLVENT
Date: 26.03.07
Page 1 of 2

For Professional Use Only

Product Code SOL5, SOL10, SOL20, SOL200
Packaging 4ltr cans, 10ltr pail, 20ltr pails, 200ltr drums
Description Water white liquid with pungent odour; flammable

Use Lustre Seal Solvent is useful in cleaning apparatus that has been clogged or contaminated with a range of paints and coatings. Solvent can be used to dilute Super Bond, Acrylic Sealer, High Build, Dcs Sealer, Expo Sealer, Covatex Sealer, M20, Ua20 & M90.

Application Apply to existing concrete to clean off certain greases and other contaminants before sealer application with a soft broom. Normal use of Lustre Seal Solvent as a dilutant with any of the mentioned sealers between 10%-50% to aid penetration of concrete surfaces. Add slowly while stirring until thoroughly mixed.

If too much Lustre Seal Solvent is used to dilute, coatings will end up being too thin in film build, necessitating the need for multi coats to build up protection and gloss.

Usage Rate Refer to Tech Data sheet for each sealer mentioned.

Specifications

Chemical Nature:	Aromatic Hydrocarbon Solvent
Cas No:	1330-20-7
Flash Point (closed cup):	24°Celsius T.C.C.
Boiling Point:	137.5°C
Density @ 20°C:	0.87
Solubility in Water:	Immiscible
Explosive Limits:	Lower 1% - Upper 6%

Features Excellent Solubility
Colourless
Non-Foaming

Limitations Flammable
Harmful material when used wrongly.
Not suitable for water based systems.

Storage Store in a cool, dry area and keep container sealed.

Shelf Life 2 years, if kept in unopened container and stored in cool, dry conditions. After this time, the product should be checked for its suitability for use.



Solvent

Reference: TDSOLVENT
Date: 26.03.07
Page 2 of 2

Disposal

Only by local licenced contractor for hazardous substances or as required by local authority.

Precautions

Before using, read Material Safety Data Sheet for this product. Ensure suitable protective clothing is worn (mask, gloves, goggles and overalls). Poisonous. Keep out of Reach of Children. Breathing the vapour is dangerous. Provide adequate ventilation during application. Always allow rags used with solvent to dry before disposing, as self-ignition could occur causing a fire. Caution should be taken when using electric drills as they can produce sparks which could cause ignition. Do not use in the presence of a naked flame. Do not smoke. Electrostatic charge maybe charged during handling eg. Pumping, in case of fire, carbon dioxide, dry chemical powder, foam, sand or earth should be used, but not water jets. Do not smoke. Prolonged and repeated skin contact can cause dermatitis.

PARCHEM CONSTRUCTION SUPPLIES PTY LTD has no control over the use or storage of this product and therefore does not accept any liability in this regard. Any verbal advice given should NOT be regarded as authoritative information. This information is subject to change without notice, therefore, all applicators should ensure they have up to date information. This product is intended for use only by skilled tradesman and where applicable statutory licensed tradesman, experienced and trained in the use of this product. This product is warranted to be of uniform quality within the manufacturer's tolerances. The manufacturer has no control over the use or misuse of this product; therefore, no warranty expressed or implied, is or can be made either as to the effects or results of such use. The manufacturer's obligations shall be limited to replacing product proven to be defective. Please refer to our terms and conditions of sale